IGL COATINGS™ ECOCOAT EZ



Specification 154325 Revision date 08.06.2022

Version **3.01** Page 1 of 7



IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME : IGL Coatings™ ecocoat EZ

FUNCTION : Hydro & oleophobing and easy clean agent surface modifier

COMPANY : Ominent Sdn Bhd

ADDRESS : No.7, Jalan Majistret U1/26, Hicom-Glenmarie Industrial Park, Seksyen U1, 40150 Shah Alam,

Selangor.

PHONE : +60355690980

EMAIL ADDRESS : regulations@iglcoatings.com

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Physical hazards

Flammable liquid Category 3

Health hazards

Skin irritation Category 2
Serious eye damage Category 1
Specific target organ toxicity – single exposure Category 3
Aspiration Hazard Category 1

2.2 Label Elements

Regulation (EC) No. 1272/2008







GHS05



CHCU8

Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

H317 Causes skin irritation

H318 Causes serious eye damage

H336 May cause drowsiness or dizziness

Precautionary statements

P210	Keep away [,]	from heat,	/sparks/d	open flames,	/hot sur	taces. No	smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P261 Avoid breathing dust/fume/gas/vapours.
 P264 Wash exposed skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/attention.

IGL COATINGS™ ECOCOAT EZ



Material no.

 Specification
 154325
 Revision date
 08.06.2022

 Version
 3.01
 Page
 2 of 7

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use water spray, dry chemical or carbon dioxide to extinguish.

P403+P235 Store in well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to comply with local, state and federal regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS No	Chemical Name					
	EC No	Index No	REACH No			
	Classification according to Regulation (EC) No. 1272/2008 (CLP)					
64742-47-8	Distillates (petroleum), hydrotreated light					
	265-149-8	Not applicable	Not applicable			
	Flam. Liq. 4; H227: Asp. Tox. 1: H304					
123-86-4	Butyl acetate					
	204-658-1	607-025-00-1	01-2119485493-29-0000			
	STOT SE 3: H336; Flam. Liq. 3: H226					
475645-84-2	Organopolysilazane					
	Not applicable	Not applicable	Not applicable			
	Acute Tox. 4: H302; Flam. Liq. 2: H225; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1: H317					
63148-61-8	Organopolysiloxane					
	814-597-8	Not applicable	Not applicable			
	Not applicable					
7782-42-5	Graphene					
	231-955-3	Not applicable	01-2119486977-12-0000			
	Not applicable					

Additional information:

The exact percentage of some ingredients used in this product are considered to be proprietary and are withheld as confidential business information.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General Information

Take off contaminated clothing.

After Inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

After skin contact

Gently wash with plenty of soap and water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water at least 15 minutes. Remove contact lenses, if presence and easy to do In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Do not induce vomiting. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

IGL COATINGS™ ECOCOAT EZ



Specification 154325 Revision date 08.06.2022

Version **3.01** Page 3 of 7



In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media

Water fog, dry chemical or carbon dioxide.

5.2 Unsuitable extinguishing media

High volume water jet.

5.3 Special hazards arising from the substance or mixture

Hazardous toxic and irritating fumes or smoke may be emitted

Vapours may travel considerable distance to ignition source and flash back.

Hazardous Combustion Products: Incomplete combustion products, Oxides of carbon, Smoke, Fume

5.4 Advise for firefighters

As in any fire, wear self-contained positive-pressure breathing apparatus, (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition

Beware of vapours accumulating to form explosive concentrations. Vapour can accumulate in low areas.

Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

Take up mechanically.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated articles and floor according to the environmental legislation.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Do not breath vapour/dust. Avoid contact with eyes. Wash thoroughly with water and soap after handling.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge

Further information on handling

General protection and hygiene measures: refer to section 8.

7.2. Conditions for safe storage, including any incompatibilities

Further information on handling

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Do not store together with food and feeding stuffs.

Further information on storage conditions

IGL COATINGS™ ECOCOAT EZ



Material no.

Specification 154325 Revision date 08.06.2022

Version **3.01** Page 4 of 7

Keep the packing dry and well-sealed to prevent contamination. Recommended storage temperature: 20C Protect against: UV-radiation/sunlight. heat.

Static electricity may accumulate and cause a fire hazard

7.3. Specific end use(s): refer to section 1.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional Information: The lists valid during the making were used as basis.

8.2 Exposure Control

Advice on safe handling

8.2.1 General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Ensure adequate ventilation.

8.2.2 Personal protective equipment:

Respiratory protection: Required when aerosols are generated. Recommended filter type: ABEK filter **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of protective clothing should take into account all relevant work factors such as: other chemicals which may be handled, physical requirements, etc.

Material of gloves:

Butyl rubber.

Penetration time of glove material:

> 10 min

Eye protection: Tightly fitting eye goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point : 126 °C

Vapour Pressure: 10.66 hPa (at 20°C)Relative Vapor Density: 4.0 (Air = 1)Specific Gravity: No data availableMelting Point: Not applicable

Flash Point : 58°C

pH : No data available
Evaporation Rate : Not applicable
Solubility in Water : Not soluble
Appearance (colour) : Transparent black

Appearance (form) : Liquid
Odour : Ester-like

10. STABILITY AND REACTIVITY

10.1 Reactivity: No further relevant information available.

10.2 Chemical stability: Stable under normal conditions.

Thermal decomposition / conditions to avoid: No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions**: No dangerous reaction known under conditions of normal use.
- **10.4 Conditions to avoid**: Sunlight, heat, open flames, high temperature, sparks, static electrical charge, other ignition sources
- **10.5 Incompatible materials**: Strong oxidizing agents.
- 10.6 Hazardous decomposition products: Possible decomposition products in case of hydrolysis: Hydrogen,

IGL COATINGS™ ECOCOAT EZ



Specification 154325 Revision date 08.06.2022

Version **3.01** Page 5 of 7



ammonia, condensed siloxane.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects: No data available. **Skin corrosion/irritation:** May causes skin irritation.

Eye irritation: May cause eye damage.

Respiratory or skin sensitization: No information available.

Summary of evaluation of the CMR properties: Shall not be classified as a germ cell mutagenic, carcinogenic nor as a

reproductive toxicant.

Specific target organ toxicity - single exposure: Category 3. May cause drowsiness and

dizziness.

Specific target organ toxicity – repeated exposure: No information available.

Aspiration hazard: May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Volume of ingredients used does not trigger toxicity classifications under the Globally Harmonized System of Classification and Labelling of Chemicals.

12.2 Process of degradability

No data available.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB Assessment

No data available.

12.6 Other adverse effects

Discharge into the environment must be avoided.

13. DISPOSAL CONSIDERATION

13.1 Waste treatment methods

Dispose of contents/container in accordance with local/regional/national/international regulation.

Sewage disposal-related information

Do not empty into drains.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

14. TRANSPORT INFORMATION

14.1 IATA-DGR

UN number : 1263

UN proper shipping name : Paint-related materials

Transport hazard class(es) : 3
Packing group : III
Environmental hazards : No
Special precautions for user : Remarks : -

14.2 IMDG-Code

UN number : 1263

IGL COATINGS™ ECOCOAT EZ



Material no.

Specification 154325 Revision date 08.06.2022 Version 3.01 Page 6 of 7

UN proper shipping name : Paint-related materials

Transport hazard class(es) : 3
Packing group : III
Environmental hazards : No
Marine pollutant : No
EmS Code : -

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture US Federal Regulations

US. Toxic Substances Control Act (TSCA)

All chemical substances in this material are included on the TSCA Inventory of Chemical Substances.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Hazardous Substance List

This product contains the following substance subject to the reporting requirements of CERCLA Hazardous Substance List

Component(s)Butyl acetate
123-86-4

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Emergency Planning and Community Right-To-Know Act (EPCRA) Section 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

Emergency Planning and Community Right-To-Know Act (EPCRA) Section 313 Toxics Release Inventory (TRI) Reporting

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CRF 68.130)

None present or none present in regulated quantities.

US. State Regulation

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

EU Regulation

EU. Directive 2012/18/EU (SEVESO III) on Major Accident Hazards Involving Dangerous Substances, Annex I:

Not applicable.

Korea Regulations

KECI: All chemical substances in this material are included and in compliance with the KECI inventory. K-REACH: None present or none present in regulated quantities.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SAFETY DATA SHEET IGL COATINGS™ ECOCOAT EZ

Material no.

Specification 154325 Revision date 08.06.2022

Version **3.01** Page 7 of 7



Further information

Changes since the last version are highlighted in the margin. This version replaces all previous versions. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material use in combination with any other materials or any process, unless specified in the test.